



Linear mode regulation
 Overload and short circuit protected
 Current limiter
 Thermo protection
 DIN EN 50022 rail mounting

Voltage input : 230V AC \pm 10% 50Hz, 60Hz
Stabilität : \leq 0,1 V
Ripple : \leq 5 mV
Protection : IP 20
Safety : EN 60010 Class III
High-voltage test 3,75V_{eff} , 1 min (input – output)
Operating temperatur : 0 – 50 °C
Size : 115 x 77 x 32 mm (4W), 115 x 77 x 55 mm (10W)

	OUTPUT POWER: 4 W	OUTPUT POWER: 10 W
OUTPUT VOLTAGE: 5 V	OUTPUT CURRENT: 0,80 A	OUTPUT CURRENT: 2,00 A
OUTPUT VOLTAGE: 10 V	OUTPUT CURRENT: 0,40 A	OUTPUT CURRENT: 1,00 A
OUTPUT VOLTAGE: 12 V	OUTPUT CURRENT: 0,33 A	OUTPUT CURRENT: 0,83 A
OUTPUT VOLTAGE: 15 V	OUTPUT CURRENT: 0,26 A	OUTPUT CURRENT: 0,66 A
OUTPUT VOLTAGE: 24 V	OUTPUT CURRENT: 0,16 A	OUTPUT CURRENT: 0,41 A

